

Parts of machine Mainly Body

Seals	Hallite (England)
Cylinder	China
Motor	China
Pump	China
Steel	Bao Steel
Hydraulic Part	Japan brand in China
Electrical components	DELIXI (Germany brand in China)
Tubing /pipe	China

Widely applied by second-hand clothes recycling plants for compressing clothing, comforters, shoes etc. Hydraulic lifting chamber door improves the work efficiency, conveniently for packaging and the tight crossed tying.

Features

- Hydraulic lifting chamber door improves the work efficiency, conveniently for packaging and the '# 'tying
- The ram will stop running downwards when the feeding gate is opened which ensure the safety of the operation
- Equipped with independent emergency stop for safe operation
- Special ram guides design makes the platen not slope because of uneven materials feedings during compression

Model	NK120LT
Hydraulic power	120Ton
Packaging size (L*W*H)	1000*700*1250-1350 mm
Feed opening size (L*H)	1000*600mm
Chamber Size (L*W*H)	1000*800*1860 mm
Bale weight	300-500Kg
Capacity	10-12 bale /H
System pressure	25Mpa
Packing materials	Cross packing
Packing way	Front-Back 5 pcs/ Left-Right 2 pcs
Voltage	380V/50HZ
Power	18.5KW/25HP
Machine size (L*W*H)	1750*1200*5060mm