

压配式实心轮胎 Press-on Solid Tires



序号 No.	轮胎规格 Size of Tire		花纹种类 Types of Pattern	轮胎重量 Net Weight(Kg)	最大负荷 Max Load (Kg)				
	英制	公制			平衡式叉车 Counter Balance Lift Trucks				Other Industrial Vehicles
	Inch	Millimeter	10km/h		16km/h		16km/h		
	(in)	(mm)	驱动轮 Driving	转向轮 Steering	驱动轮 Driving	转向轮 Steering			
1	9x5x5	228.6x127x127	SM	6.50	890	790	785	715	685
2	10x4x6 1/2	254x101.6x165.1	SM	6.00	720	640	635	580	555
3	10x5x6 1/2	254x127x165.1	SM	7.40	940	835	830	755	725
4	10x6x6 1/2	254x152.4x165.1	SM	9.00	1160	1035	1030	935	895
5	10 1/2x5x5	266.7x127x127	SM	8.00	1020	910	905	820	785
6	10 1/2x6x5	266.7x152.4x127	SM	10.40	1295	1155	1145	1040	995
7	10 1/2x5x6 1/2	266.7x127x165.1	SM	8.20	1000	890	885	805	770
8	10 1/2x6x6 1/2	266.7x152.4x165.1	SM	9.60	1240	1105	1100	995	955
9	12x4 1/2x8	304.8x114.3x203.2	SM	8.60	970	865	860	780	745
10	13 1/2x5 1/2x8	342.9x139.7x203.2	SM	13.00	1400	1245	1235	1125	1075
11	14x4 1/2x8	355.6x114.3x203.2	SM/TR	12.20	1085	965	960	870	835
12	15x5x11 1/4	381x127x285.8	SM	12.60	1290	1150	1145	1040	995
13	15 1/2x5x10	393.7x127x254	SM	14.00	1365	1215	1210	1100	1050
14	15 1/2x6x10	393.7x152.4x254	SM	16.80	1735	1545	1535	1395	1335
15	16x5x10 1/2	406.4x127x266.7	SM	16	1400	1245	1240	1125	1075
16	16x6x10 1/2	406.4x152.4x266.7	SM	19.27	1775	1580	1570	1430	1365
17	16x7x10 1/2	406.4x178.8x266.7	SM	21.1	2155	1915	1905	1730	1655
18	16 1/4x5x11 1/4	412.8x127x285.8	SM/TR	14.60	1415	1260	1250	1135	1090
19	16 1/4x6x11 1/4	412.8x152.4x285.8	SM/TR	17.60	1780	1585	1575	1480	1370
20	16 1/4x7x11 1/4	412.8x177.8x285.8	SM	20.00	2150	1915	1900	1730	1655
21	17x5x12 1/8	431.8x127x308	SM	16.00	1460	1300	1295	1175	1125
22	18x5x12 1/8	457.2x127x308	SM/TR	18.00	1525	1355	1350	1225	1175
23	18x6x12 1/8	457x152x308	SM	23.5	1945	1735	1720	1565	1500
24	18x7x12 1/8	457x178x308	SM	28.03	2370	2110	2095	1905	1820
25	18x8x12 1/8	457x203.2x308	SM	30.10	2790	2485	2470	2245	2145
26	18x9x12 1/8	457.2x228.6x308	SM/TR	32.00	3215	2860	2840	2580	2470
27	20x8x16	508x203.2x406.4	SM/TR	28.40	2795	2490	2475	2250	2150
28	21x7x15	533.4x178.8x381	SM/TR	33.6	2665	2370	2355	2140	2050
29	21x8x15	533.4x203.2x381	SM	38.6	3140	2795	2780	2525	2415
30	21x9x15	533.4x228.6x381	SM	41.00	3620	3220	3200	2910	2785
31	22x8x16	558.8x203.2x406.4	SM/TR	38.00	3255	2895	2880	2615	2500
32	22*9*16	559x229x406	SM	43.00	3745	3335	3315	3010	2880
33	22x12x16	559x305x406	SM	62.00	5230	4655	4625	4205	4025
34	26x10	660x250 (x480)	SM	68	4810	4290	4580	4240	3700
35	28x12x22	711x304x558.8	SM	79.3	6265	5575	5545	5035	4820
36	28x16x22	711.2x406.4x558.8	SM	110	8635	7685	7640	6940	6645

Our Press-on solid tires fit for the following popular forklift brands



Our press-on tire pattern and color



Press-on tires are applicable for the industrial vehicles running on the smooth road. It has characteristics as follows:

1. Low barycenter
2. Lower energy consumption
3. Anti-puncture
4. Lower maintenance cost
5. Higher density of rubber
6. Higher wear resistance
7. Good stability
8. Tire base is made to combine with steel wheel very tightly so as to avoid peeling off between them.

