






Cycle	Cycles	65535	
	Steps	254	
	Nested Function	Max three levels of loops	
Protective Function		<ul style="list-style-type: none"> <li>• Power-off data protection</li> </ul>	
		<ul style="list-style-type: none"> <li>• Off-line Operating</li> </ul>	
		<ul style="list-style-type: none"> <li>• User-defined safety (upper and lower) tolerance of current, voltage and delay time</li> </ul>	
		Reverse-connecting protection	
Channel Features	Independent pairs of closed loop for constant current source and constant voltage source		
Channels	Independent control		
Detection and Sampling	4-wire Connecting		
Noise Density	<85dB		
Data Management	MYSQL Database		
Communication Means	TCP/IP Protocol		
Exports Formats	EXCEL, TXT, Graph		
Communication Interface	Ethernet Port		
Number of Channels Per Cabinet	8		
<b>Operating Environment</b>			
Description	Product Specification		
Operating Temperature	0°C~40°C		
Storage Temperature	-10°C~50°C		
Operating Humidity	≤70% RH		
Storage Humidity	≤80% RH		
Description	Product Specification		
Battery Holder	Universal Holder		
Holder Picture(You can choose one kind of holder based on your battery)			
	Alligator Holder	Polymer Holder	Wiring Terminal
	Picture for reference, please confirm the actual product		
Dimensions (W*D*H) (mm)	3U (164) ,480*330*130		

Equipment Picture



Picture for reference, please confirm the actual product