






Cycle	Cycles	65535	
	Steps	254	
	Nested Function	Max three levels of loops	
Protective Function		<ul style="list-style-type: none"> <li>• Power-off data protection</li> </ul>	
		<ul style="list-style-type: none"> <li>• Off-line Operating</li> </ul>	
		<ul style="list-style-type: none"> <li>• User-defined safety (upper and lower) tolerance of current, voltage and delay time</li> </ul>	
		Reverse-connecting protection	
Channel Features		Independent pairs of closed loop for constant current source and constant voltage source	
Channels		Independent control	
Detection and Sampling		4-wire Connecting	
Noise Density		<85dB	
Data Management		MYSQL Database	
Communication Means		TCP/IP Protocol	
Exports Formats		EXCEL, TXT, Graph	
Communication Interface		Ethernet Port	
Number of Channels Per Cabinet		4	
<b>Operating Environment</b>			
Description		Product Specification	
Operating Temperature		0°C~40°C	
Storage Temperature		-10°C~50°C	
Operating Humidity		≤70% RH	
Storage Humidity		≤80% RH	
Description		Product Specification	
Battery Holder		Universal Holder	
Holder Picture(You can choose one kind of holder based on your battery)			
			
		Alligator Holder	Polymer Holder
	Picture for reference, please confirm the actual product		
Dimensions (W*D*H) (mm)		24U, 600*600*1260	

Equipment Picture



Picture for reference, please confirm the actual product