

IDM-156W

15.6" Wide screen Full HD LCD industrial panel monitor



Features

- 15.6" wide Full HD LCD Panel support 1920 x 1080 pixels, 400 cd/m2 brightness
- 6mm Aluminum bezel panel with touch screen/strengthen glass
- Flat, sealed and modularized design
- Direct VGA, HDMI input interfaces
- OSD control keys to optimize the display (Optional)
- Power adapter with AC 100 V ~ 240 V input and DC +12 V output
- Optional 9 ~ 36 VDC power input
- NEMA4 / IP 65 compliant front panel
- Supports panel, wall, desktop, rack or VESA arm mounting

Specifications

LCD Panel	
Display Type	15.6" Wide Full HD LCD
Max.Resolution	1920 x 1080
Max.color	16.7M
Luminance	400 cd/m2
View Angle	160°(H) , 140°(V)
Contrast Ratio	700:1
Response Time	8 ms
Backlight Life	50,000hrs
System	
Touch screen(optional)	Resistive touch screen(RS232/USB)
Input Signals	VGA, HDMI/DVI, Audio
Power Supply	100~240VAC,50/60Hz, DC12V@ 5A / 60W ,external ac adapter
DC Power (Optional)	DC 9~ 36v input power module

Mechanical and Environmental	
IP level	NEMA4 / IP 65 front panel
Operate temperature	0 °C to 50 °C
Storage temperature	-20 °C to 60 °C
Storage humidity	10% to 90% non-condensing
Anti-Vibration	17HZ-500 HZ 1G PTP
Anti-Shock	1G / peak(11m sec)
Dimensions (WxHxD)	402x 252 x 45 mm
Weight	Net: 7.5kg , Gross:9.0 kg

Ordering Informations

IDM-156W	15.6" wide Full HD LCD 1920 x 1080 industrial monitor with VGA, HDMI input
IDM-156WT	15.6" wide Full HD LCD 1920 x 1080 Industrial Monitor with VGA , HDMI, Touch screen

Dimensions Diagram

