







Dongguan Fvwin Electronics Co.,Ltd

Email:fvwin@fvwin.com Skype:evelynhwang2013

http://www.fvwindz.com

Illuminated Button Switch						
Pic						
Model	TS15-9W56WTX	TS15-10W57WTX	TS15-12W58WBX	PB12-23WXX	PB15-23WXX	PB17-22WXX
Size(mm)	12(L)*12(W)*13.1(H)	15(L)*15(W)*12.7(H)	16(φ)*13.1(H)	12(L)*12(W)*23(H)	15(L)*15(W)*23(H)	17.4(L)*17.4(W)*22.65(H)
Circuit	SPST Momentary	SPST Momentary	SPST Momentary	OFF-(ON)/Momentary SPST	OFF-(ON)/Momentary SPST	SPST
Rating	50mA 12VDC	50mA 12VDC	50mA 12VDC	100mA 12VDC	100mA 12VDC	100mA 12VDC
Electrically Life	2,00,000 Cycles Min	2,00,000 Cycles Min	2,00,000 Cycles Min	1,000,000 Cycles Min	1,000,000 Cycles Min	100,000 Cycles Min
Actuation Force	250±50gf	250±50gf	250±50gf	250±100gf	250±100gf	250±100gf
Total Travel	0.4±0.15mm	0.4±0.15mm	0.4±0.15mm	4.5±0.2mm	4.5±0.2mm	4.5±0.2mm

Feature:

1. Available in three different cap sizes of 12 mm, 15 mm,16mm and 17.4 mm
2. Sculpted Clear Cap style or Laser etch on clear lens for design flexibility in audio/video applications
3. Available with super bright red,green,blue or RGB LED
4. A best solution for all broadcast and Pro A/V panel need