



ISO9001 &amp; CE Certificate

**LTF-1131**

Long Emergency Lightbar

**SPECIFICATION :**

- Feature: 4 Rotating light
- Voltage: DC12V/DC24V
- Length: 1214mm
- Chassis material: Aluminum
- Working Temperature: -40°C ~ +50°C
- Lifetime: >50000hrs
- Material of lens: Polycarbonate (PC)
- Dome Color: Blue/Red, Blue/Blue, Red/Red, Amber/Amber, Clear/Clear
- Size: 1214\*296\*95mm
- Mass: 1250\*370\*260mm
- N.W./W: 12/11KGGS

**LTF-1156**

Long Emergency Lightbar

**SPECIFICATION :**

- Feature: 5 Rotating light
- Voltage: DC12V/DC24V
- Length: 1314mm
- Chassis material: Aluminum
- Size: 1214\*296\*95mm
- Mass: 1250\*370\*260mm
- Working Temperature: -40°C ~ +50°C
- Lifetime: >50000hrs
- Material of lens: Polycarbonate (PC)
- Dome Color: Blue/Red, Blue/Blue, Red/Red, Amber/Amber, Clear/Clear
- N.W./W: 12/11KGGS



ISO9001 &amp; CE Certificate

**LTF-1231** Long Emergency Strobe Lightbar**LTF-1331** Long Emergency LED Lightbar**SPECIFICATION :**

- The lightbar is made from high quality polycarbonate material; the base is made from Aluminum metal alloy.
- The power supply capability is stable. The endurance of power supply module is free for whole life.
- It adopts high quality impeller strobe scope lamp with life time more than 5 millions cycles, high brightness and stability.
- Reflector adopt CAM as assistant process to heighten 20% luminous efficiency.
- With American CMOS chip of MICRO and control program by oneself design, we can control the strobescope module freely.

one off design, we can control the strobescope module freely.

- Voltage: DC12V/DC24V
- Power: 100W
- Light source: Xenon(LTF-1231)LED(LTF-1331)
- Chassis material: Aluminum
- Material of lens: Polycarbonate (PC)
- Size: 1214\*296\*95mm
- Mass: 1250\*370\*260mm
- Dome Color: Blue/Red, Blue/Blue, Red/Red, Amber/Amber, Clear/Clear
- N.W./W: 11.5/10KGGS(LTF-1231), 13.6/11KGGS(LTF-1331)

**LED4200 LED Light Bar****SPECIFICATION :**

- LED4200, a kind of luxury caution light, is our company brand product that is designed with advanced technology.
- It adopts 64 pieces (8 groups \* 8 pieces ) super brightness LEDs as front light and rear lamp source.
- The back light adopts 8 program lights and 8CH 64 built-in color.
- The light bar has many kinds such as advanced internal frame,

low power consumption, free vibration and so on.

- The chimney is made of transparent PC materials, which makes the light get higher penetrative ability.
- It is particularly fit for police, fire, great ambulance and other special fields.
- Packing size: 1225\*530\*225mm
- Net weight: 12KGGS

LTF-C1000 Motion Lightbar



LTF-C2000 Strobe Lightbar



LTF-C3000 | 乐拓光合



## SPECIFICATION:

- The lamp head is made from high-quality polycarbonate material; the base is made from aluminum metal alloy. The middle handle made from stainless steel.
  - The power supply capacity is stable. The maintenance of power supply model is free for whole life.
  - Endoptics high-quality imaging strobescopic lamp with life time more than 5 million cycles, high brightness and stability.
  - Reflector adopt C4M as assistant process to heighten 20% luminous efficiency.
  - With American C100S chip of MICRO and control program by oneself design, we can control the fibroscopic modes easily.
  - Beam 2 Single directional pulse xenon light / Triple/ 4-directional pulse xenon light/ LTF-20000, TLED/pulse lighting, TF-21000, multi-directional rotator / LTF-44000
  - Voltage DC12V/24V
  - Glassless material: Aluminum
  - Size: 180\*480\*194mm
  - Mass: 1250~1300g
  - Material of lens: Polycarbonate (PC)
  - Dome Color:  
Blue/Red, Blue/Blue, Red/Blue, Anion/Anti, Clear/Clear
  - N.W.G. W 19.6/21.3KGS

#### **LTF-8C900** Low Profile LED Lighter



**SPECIFICATION:**

- Voltage: DC 12-24V
  - The mini light panel adopts bright LED light source. It has advanced Marshall lamps and low power consumption without pollution!
  - The around material of them is made of PC for penetrative ability. Top of the light is aluminum alloy and with good appearance.
  - Color: Color: Red, Blue, White, Yellow, Green, Orange, Clear Glass
  - Size: 1050\*220\*130mm
  - Packing Size: 1130\*275\*163mm
  - Net Weight: 9kg/pc

**LTF-8C920** Low Profile LED Lightbar



**SPECIFICATION:**

- Voltage:** DC 12V/24V
  - This mini lightbox 1800lm Bright LED light source.** It has aluminum material frame and low power consumption without pollution.
  - The anodized aluminum frame is made of PC for protective ability, the light is aluminum alloy and with good appearance.**
  - Dimmable Color: 2200K-6500K Blue-Warm White-Neutral-Automatic-Cool-Color**
  - Size: 1080\*220\*130mm**
  - Packing Size: 1130\*275\*145mm**
  - Net Weight: 18KG**

**Starway**

ISO9001 & CE Certificate

**LTF-8C905** Low Profile LED Lightbar

**SPECIFICATION :**

- Voltage : DC 12/24V
- This mini lighter adopts bright Q-III LED light source. It has advanced external frame and low power consumption without pollution.
- The around material of lens is made of PC for penetrative ability. Top of the light is aluminum alloy.

**Domestic color appearance:**

- Dome Color: Blurred, Blue/Blue, Red/Red, Amber/Amber, Clear/Clear
- Size: 1000\*220\*25mm
- Packing Size: 1100\*275\*165mm
- N.W/G.W: 10.7KGS(LTF-8C905), 18.5KGS(LTF-8C905)

**Color Options:**

**LTF-8C908** Low Profile LED Lightbar

**LED3520** LED Ultimate Lightbar

**SPECIFICATION :**

- Voltage : DC 12/24V
- Dome: Imported high-strength PC material with excellent lusterous and high penetrative-for stability.
- Basis: Aluminum alloy material with high strength.
- Bulb : LED light With the functions of high brightness, fine stability, low energy consumption.
- Adopting high luminosity LEDs as front light source.
- Backlight with six programme light.

**Domestic Color:**

- Blue/Red, Blue/Blue, Red/Red, Amber/Amber, Clear/Clear

**Size:** 1000\*220\*25mm

**Packing Size:** 1100\*275\*165mm

**N.W/G.W:** 12KGS(LED3520), 18.5KGS(LTF-8C908)

**QTY PER CARTON:** 1/PC

**Color Options:**

**Starway**

ISO9001 & CE Certificate

**LED3510** LED Lightbar

**LED3512** LED Lightbar

**SPECIFICATION :**

- Voltage : DC 12/24V
- Dome: Imported high-strength PC material with excellent lusterous and high penetrating-for stability.
- Basis: Aluminum alloy material with high strength.
- Bulb : LED light With the functions of high brightness, fine stability, low energy consumption.
- Power : 100W speaker(LT3510)
- Adopting high luminosity LEDs as front light source.
- Backlight with six programme light.

**Domestic Color:**

- Blue/Red, Blue/Blue, Red/Red, Amber/Amber, Clear/Clear

**Size:** 1200\*305\*34

**Packing Size:** 1250\*350\*180

**N.W/G.W:** 16.7KGS(LED3510), 18.5KGS(LED3512)

**QTY PER CARTON:** 1/PC

**Color Options:**

**LIGHTBARS**

**LED3500** LED Lightbar

**SPECIFICATION :**

- Voltage : DC 12/24V
- Dome: Imported high-strength PC material with excellent lusterous and high penetrating-for stability.
- Basis: Aluminum alloy material with high strength.
- Bulb : LED light With the functions of high brightness, fine stability, low energy consumption.
- Adopting high luminosity LEDs as front light source.
- Backlight with six programme light.

**Domestic Color:**

- Blue/Red, Blue/Blue, Red/Red, Amber/Amber, Clear/Clear

**Size:** 1200\*305\*34

**Packing Size:** 1240\*350\*180

**N.W/G.W:** 16.7KGS

**QTY PER CARTON:** 1/PC

**Color Options:**

**LIGHTBARS**

**17**

<http://www.starwaysignal.com>

<http://www.starwaylights.com>

**18**

<http://www.starwaysignal.com>

<http://www.starwaylights.com>



LED3531 LED Lightbar




LED3522 LED Lightbar

**SPECIFICATION:**

- Voltage: DC 12/24V
- Life Span: 100,000 12/24V G-Z LEDs
- Dome: Imported high-strength PC material with excellent luster and high penetrating-for visibility
- Base: Aluminum alloy material with high strength.

- Dome Color: Blue/Red, Blue/Blue, Red/Red, Amber/Amber, Clear/Clear
- Packing Size: 1265\*350\*180mm
- QTY PER CARTON: 1PC

LTF-A800/DF LED Lightbar


**SPECIFICATION:**

- Voltage: DC 12/24V
- Life Span: 100,000 12/24V G-Z LEDs
- Dome: Imported high-strength PC material with excellent luster and high penetrating-for visibility
- Base: Aluminum alloy material with high strength.

- Dome Color: Blue/Red, Blue/Blue, Red/Red, Amber/Amber, Clear/Clear
- Packing Size: 1265\*350\*180mm
- QTY PER CARTON: 1PC



LTF-A600AB-120 LED Full Lightbar

**SPECIFICATION:**

- Voltage: DC 12V
- Light Power: 100W
- Working Current: <16.4A
- Life Span: 100,000 12/24V G-Z LEDs
- 15 Flash patterns
- Bottom: Imported high-strength PC material with excellent luster and high penetrating-for visibility

- Base: Aluminum alloy material with high strength
- Light Color: Blue/Red/Amber/White
- Dome Color: Blue/Red/Amber/Clear
- Bottom Material: Aluminum

LTF-A900AB-140 LED Full Lightbar



LTF-A921AB LED Lightbar with Siren



LTF-A900AB-120 LED Full Lightbar

**SPECIFICATION:**

- Speaker Power: 100W (LTF-A921AB)
- Reluctor: multi-flash patterns and 2 sound (maxing LTF-A911AB)
- Size: 1480\*380\*180 (mm)(LTF-A900AB-140,LTF-A921AB)
- 1260\*380\*180 (mm)(LTF-A900AB-120,LTF-A921AB)
- Packing Size: 1505\*254\*180mm(LTF-A900AB-140)
- 1260\*380\*180mm(LTF-A900AB-120,LTF-A921AB)
- N.W/G.W:16.5/17.3KG(8LTF-A900AB-140)

**Starway**

ISO9001 & CE Certificate

**LTF-A631AB-120 LED Full Lightbar**

**SPECIFICATION:**

- Voltage: DC12V or 24V
- Light source: high power 1W LED module
- Lamp colors: Red/Blue/Amber/White
- Cover color: Red/Blue/Amber/Green
- Structure: Inside 220x2 LED module, two sides

**LTF-A300AB-120 LED Lightbar**

**SPECIFICATION:**

- PC and aluminum alloy material: LED tube, energy saving, low consumption, environmental protection
- Volt: DC12V(DC24V please minus us)
- Color: Red/Blue/Amber/Clear
- LED module/LED

**LTF-A400AB-120 LED Lightbar**

**SPECIFICATION:**

- Voltage: DC12V or 24V
- The environment temperature: -40 degree~75 degree
- Light source: LED light
- Work environment: earth
- Work voltage: DC12V~DC24V

**Lightbar Colors:**

- Red/Blue
- Blue
- Red/White
- Yellow/White
- White

<http://www.starwaysignal.com>

<http://www.starwaylights.com>

**Starway**

ISO9001 & CE Certificate

**LTF-A931AB-120 Full LED Lightbar**

**LTF-A935AB-120 Full LED Lightbar**

**SPECIFICATION:**

- Life Span: 100,000 h (24V G-2/Q-5 Linear LED)
- Outer: Imported high-strength PC material with excellent tensile and high bending strength
- Base: Aluminum alloy material with high strength
- Size: 1200\*300\*136 (mm)

**LED5702 LED Lightbar**

**SPECIFICATION:**

- 8 LED modules optional
- 8 small LED module: Green or Blue/Orange/Yellow
- 2xLED alloy light or Halogen alloy light and Alternating Flash function, speaker compartment and 12 Volt coil
- 3 bulbs control box: Infrared Radio on board
- Size: 1200\*385\*210mm
- Color: Red/Blue/All Red/All Blue/All Amber/All Clear and emergency combination

<http://www.starwaysignal.com>

<http://www.starwaylights.com>

**Starway**

ISO9001 & CE Certificate

**LTF5450 LED Lightbar**

**LTF5550 LED Lightbar**

**LED5601 All Direction LED Lightbar**

**SPECIFICATION :**

- Voltage : DC 12/24V
- Left alley-light: 23W halogen
- Right alley light: 23W halogen
- Frontlights: 23W\*2PCS halogen
- Emergency lights: 9.4W\*8PCS LED
- Main headlights: 5.4W\*16PCS LED, 4 knots flash mode
- Size : 1180\*314\*137(165)mm
- Net Weight: 22KGS

**FRONT VIEW**

**REAR VIEW**

**SPECIFICATION :**

- 10 LED modules with alternating flash pattern
- 8 LED rear traffic advisor
- 2 halogen turn-down lights
- 2 halogenalley lights, each controlled independently
- Warm white reflectors for increased visibility
- Aerodynamic design with hard-coated finish
- Includes universal mounting kit and 8 button control box
- Size: 1180\*315\*145(±16)mm

**Starway**

ISO9001 & CE Certificate

**LTF-8D900 LED Lightbar**

**SPECIFICATION :**

- The 1.2m full-size lightbar adopts PC boards structure and series design, which has distinct outline stronger precision-resistant capability, and is not easy to leave color and get aged.
- Built-in big power LED light source and with strong light effect, low power loss.
- It also has good feature of long service life, super bright, strong back ground light resistance, and powerful penetrating ability, good warning effect and wide application.

**LTF-8E900 LED Lightbar**

**LTF-8F900 LED Lightbar**

**FRONT VIEW**

**REAR VIEW**

**SPECIFICATION :**

- Voltage : DC 12/24V
- LTF-8E900 adopts bright 8\*4W 4 LED one module light engine
- LTF-8F900 adopts bright 8\*8W 9 LED one module light source
- It has advanced internal frame and low-power consumption

**FRONT VIEW**

**REAR VIEW**

**SPECIFICATION :**

- This product adopts double-layer aluminum alloy light bar structure
- It has distinct outline stronger precision-resistant capability
- It has good sealing and waterproof
- A lot of LED lights are distributed sharply and use high power LED lights for it give out strong flash light from each direction
- It has advantage with high brightness and low power waste
- It has 12 knots flash pattern and less colors direction lights
- It can be installed on all kinds of special vehicles
- Even in extremely complicated circumstances, it can transmit emergency signal correctly
- Voltage: 12/24V and the max. lightened load is > 800X
- The length of the light bar is 1.8M
- Working current: 0.3A(max) and Total power: 75.6W

**24**

<http://www.starwaysignal.com>

<http://www.starwaylights.com>



ISO9001 &amp; CE Certificate

**LTF-8M905** LED Lightbar**LTF-8M939** LED Lightbar**LTF-8M949** LED Lightbar**SPECIFICATION (LTF-8M905/LTF-8M939/LTF-8M949):**

- All High Intensity Gen 3.5 LED modules
- 4 To 1 Watt LED and Built-in amber strobe
- Ultra slim profile and clear lens for stealth look
- Choose from 8 flash patterns
- Ideal for fire trucks, tow truck and over-sized vehicles
- Includes gutter style mounting kit and control box

**LTF-8M925** LED Lightbar**LTF-8M927** LED Lightbar**LTF-8M929** LED Lightbar**SPECIFICATION (LTF-8M925/LTF-8M927/LTF-8M929):**

- All High intensity Gen 3.5 LED modules
- Ultra slim profile and clear lens for stealth look
- 3 To 1.5 Watt LEDs
- Choose from 8 flash patterns
- Built-in amber strobe
- Ideal for fire trucks, tow truck and over-sized vehicles
- Includes gutter style mounting kit and control box



ISO9001 &amp; CE Certificate

**LTF-B700-120** LED Lightbar**SPECIFICATION:**

- Frame: aluminum alloy material with good impact ability
- Level: polycarbonate with fire plating to strengthen heat-resist, fire-resist >400 temperature >3 color reflective mirror available
- Light source: Premium LED tube with warm white, including 100% power LED lamp normal 160 mil-2000 bridge style strobe
- IP pass: driving circuit with less energy consume, shining

- Bright until long life
- Lightbar can be controlled by light control switch or alien panel
- Size: 1200x320x120x45 mm
- Packing Size: 1250x350x200 mm
- Net Wt: 1.1kg
- QTY PER CARTON: 1pc

**LTF-B800-120** LED Lightbar**SPECIFICATION:**

- Life Span: 100,000 120-6V
- Power: 10W (10 BHCS 1.6D) in one module, 18 flash patterns to pick from
- Color: Imported high-strength PC material with excellent hardness and high penetrating force etc.

- Base: Aluminum alloy material with high strength
- Cigarette lighter can be installed and plated for police tire and construction vehicle lighting
- Switch box control the brightness
- Size: 1200x280x155mm
- Net weight: 1.0kg

**LED308** LED Wall Lighter**SPECIFICATION:**

- 6 LED modules with automatic alternating flash pattern
- Cigarette adapter (12V DC)
- Shoulder magnet light mount includes 2 button control box
- The magnetic lighters are not resistant to water or shock speed faster than 45000
- Available in Amber, Blue, Red, Green and Clear
- Size: 200x180x70mm